

KENWOOD

Listen to the Future



TK-2180/3180

VHF/UHF FM Portable Radios

FleetSync[®]
by KENWOOD

GENERAL FEATURES

- 5 W (136-174 MHz) Models
- 5 W (450-520, 400-470 MHz) Models
- Conventional & LTR[®] Zones
- 12 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- 3-Digit Sub-Display
- Function / Status LCD Icons
- RSSI Indicator
- Date & 12/24 Hour Time Clock
- Transmit / Busy / Call Alert / Warn LED
- 4 Front Panel PF keys
- 2 Side PF Keys
- Orange Emergency / AUX Key
- 12-Key DTMF / PF Keypad¹
- 500 mW Audio Power
- Enhanced Kenwood Audio
- Companded Audio
- VOX Ready
- Voice Inversion Scrambler Built-in
- Encryption / ANI Board Control
- Easy Option Port
- VGS-1 Voice Guide / Storage Option
- Emergency Call Features
- Emergency Man-Down Option
- DTMF Encode / Decode²
- Special Alert Tone Patterns³
- Call Key⁴
- Time Out Timer
- Busy Channel Lockout
- LCD Battery Status Indicator
- Low Battery Alert
- Battery Saver

- Weather-sealed ACC Connector
- MIL-Spec Speaker Mic Option
- Windows[®] Programming & Tuning⁵
- Windows[®] Firmware Uploading⁵
- Front Panel Test/Tune
- Cloning
- MIL-STD-810 C/D/E/F
- MIL-STD "Driven-Rain"
- IP-54/55 Water & Dust Intrusion
- Intrinsically Safe Option

CONVENTIONAL ZONES

- 512 Channels / 128 Zones⁶
- QT / DQT
- Two-Tone Decode⁷
- Single / Two-Tone Encode⁷
- Operator Selectable Tone⁷
- Dual Priority Scan
- Single & Multi-Zone Scan
- List Scan

TRUNKED ZONES

- 512 GID / 128 Zones⁶
- Kenwood LTR[®] Features⁸

FleetSync[®]

- FleetSync[®] or FleetSync[®] II⁹
- PTT ID Digital ANI
- Selective Call & Group Call
- Status Messaging
- Emergency Status
- Caller ID Display
- Short Text Messages¹⁰
- Power On/Off Status Messages
- PC Serial Interface

*Two models available:
With or without keypad.
(Not actual size proportion)*



Options

| | | | |
|--|--|--|--|
| <ul style="list-style-type: none"> ■ KNB-31A Ni-Cd Rechargeable Battery Pack (1700 mAh) ■ KNB-32N Ni-MH Rechargeable Battery Pack (2500 mAh) ■ KNB-33L Li-ion Rechargeable Battery Pack (1700 mAh) ■ KSC-32 Tri-chemistry Rapid Charger ■ VGS-1 Voice Guide & Storage Unit | <ul style="list-style-type: none"> ■ KRA-22 VHF Helical Antenna ■ KRA-23 UHF Helical Antenna ■ KRA-26 VHF Helical Antenna ■ KRA-27 UHF Whip Antenna ■ KRA-16 VHF Stubby Antenna ■ KRA-17 UHF Stubby Antenna ■ KRA-25 VHF High Gain Antenna | <ul style="list-style-type: none"> ■ KMC-25 Speaker Microphone ■ KEP-1 Heavy Duty Earphone ■ KHS-11 2-Wire Palm Mic with Earphone ■ KHS-12 3-Wire Mini Lapel Mic with Earphone | <ul style="list-style-type: none"> ■ KHS-14 Lightweight Single Muff Headset ■ KHS-15-BH Heavy Duty Behind-the-Head Headset ■ KHS-15-OH Heavy Duty Over-the-Head Headset ■ KBH-10 Low Profile Belt Clip ■ KBH-11 Belt Clip (2.5") |
|--|--|--|--|

Specifications

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

| Model | TK-2180 | TK-3180 |
|---|--|--------------------|
| GENERAL | | |
| Frequency Range | | |
| Type 1 | 136-174 MHz | 450-520 MHz |
| Type 2 | | 400-470 MHz |
| Number of Channels* | | |
| Zone | | Max. 128 per Radio |
| Ch/GID | | Max. 250 per Zones |
| | (Max. 512 [Conv. Ch's + GID's] total per Radio) | |
| Channel Spacing | | |
| Wide | 25, 30 kHz | 25 kHz |
| Narrow | 12.5, 15 kHz | 12.5 kHz |
| Battery Voltage | 7.5 V DC ± 20 % | |
| Battery Life (5-5-90 duty cycle, during hi-power) | | |
| with KNB-31A (1700 mAh) | Approx. 9 hours | |
| with KNB-32N (2500 mAh) | Approx. 14 hours | |
| with KNB-33L (1700 mAh) | Approx. 10 hours | |
| Operating Temperature Range | -22 °F ~ +140 °F (-30 °C ~ +60 °C) [+14 °F ~ +140 °F (-10 °C ~ +60 °C) when KNB-32N/33L in use] | |
| Frequency Stability | ±0.00025 % (-22 °F ~ +140 °F) | |
| Antenna Impedance | 50 Ω | |
| Channel Frequency Spread | | |
| Type 1 | 38 MHz | 70 MHz |
| Type 2 | | 70 MHz |
| Dimensions (W x H x D), Projections not included | | |
| Radio Only | 2-5/16" x 5-3/8" x 7/8" (58 x 136 x 21.5 mm) | |
| with KNB-31A | 2-5/16" x 5-3/8" x 1-9/16" (58 x 136 x 39.5 mm) | |
| with KNB-32N | 2-5/16" x 5-3/8" x 1-9/16" (58 x 136 x 39.5 mm) | |
| with KNB-33L | 2-5/16" x 5-3/8" x 1-5/16" (58 x 136 x 33 mm) | |
| Weight (net) | | |
| Radio Only | 9.17 oz. (260 g) | |
| with KNB-31A | 18.70 oz. (530 g) | |
| with KNB-32N | 19.75 oz. (560 g) | |
| with KNB-33L | 14.1 oz. (400 g) | |

| Model | TK-2180 | TK-3180 |
|--|--------------------------------------|---------------|
| GENERAL | | |
| FCC ID | | |
| Type 1 | ALH37323110 | ALH37333110 |
| Type 2 | - | ALH37333120 |
| IC Certification | | |
| Type 1 | 282D-37323110 | - |
| Type 2 | - | 282D-37333120 |
| RECEIVER (Measurements made per TIA/EIA-603) | | |
| Sensitivity (12 dB SINAD) | | |
| Wide | | 0.25 μV |
| Narrow | | 0.28 μV |
| Selectivity | | |
| Wide | 70 dB | 70 dB |
| Narrow | 65 dB | 63 dB |
| Intermodulation Distortion | | |
| Wide/Narrow | 70 dB (±50, 100 kHz) | |
| Spurious Response | 70 dB | |
| Audio Output (8 Ω impedance) | 500 mW with less than 3 % distortion | |
| TRANSMITTER (Measurements made per TIA/EIA-603) | | |
| RF Power Output | | |
| High | 5 W | 5 W |
| Low | 1 W | 1 W |
| Spurious Response | 70 dB | |
| Type of Emission | | |
| Wide | 16K0F3E | |
| Narrow | 11K0F3E | |
| FM Hum & Noise | | |
| Wide | 45 dB | |
| Narrow | 40 dB | |
| Audio Distortion | | |
| Wide/Narrow | 3 % | |

Kenwood follows a policy of continuous advancement in development. For this reason specifications may be changed without notice.

*Maximum capability depends on the number of programmed Zones and repeater channels.

FleetSync® is a registered trademark of Kenwood Corporation.

LTR® is a registered trademark of Transcript International.

Applicable MIL-STD & IP

| Standard | MIL 810C Methods/Procedures | MIL 810D Methods/Procedures | MIL 810E Methods/Procedures | MIL 810F Methods/Procedures |
|--|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| Low Pressure | 500.1/Procedure I | 500.2/Procedure I, II | 500.3/Procedure I, II | 500.4/Procedure I, II |
| High Temperature | 501.1/Procedure I, II | 501.2/Procedure I, II | 501.3/Procedure I, II | 501.4/Procedure I, II |
| Low Temperature | 502.1/Procedure I | 502.2/Procedure I, II | 502.3/Procedure I, II | 502.4/Procedure I, II |
| Temperature Shock | 503.1/Procedure I | 503.2/Procedure I | 503.3/Procedure I | 503.4/Procedure I, II |
| Solar Radiation | 505.1/Procedure I | 505.2/Procedure I | 505.3/Procedure I | 505.4/Procedure I |
| Rain | 506.1/Procedure I, II | 506.2/Procedure I, II | 506.3/Procedure I, II | 506.4/Procedure I, III |
| Humidity | 507.1/Procedure I, II | 507.2/Procedure II, III | 507.3/Procedure II, III | 507.4 |
| Salt Fog | 509.1/Procedure I | 509.2/Procedure I | 509.3/Procedure I | 509.4 |
| Dust | 510.1/Procedure I | 510.2/Procedure I | 510.3/Procedure I | 510.4/Procedure I, III |
| Vibration | 514.2/Procedure VIII, X | 514.3/Procedure I | 514.4/Procedure I | 514.5/Procedure I |
| Shock | 516.2/Procedure I, II, V | 516.3/Procedure I, IV | 516.4/Procedure I, IV | 516.5/Procedure I, IV |
| International Protection Standard | | | | |
| Dust & Water Protection | IP54/55 | | | |

footnotes from Front:

¹ Keypad models only.

² DTMF includes PTT ID, Emergency ANI, Manual Encode (keypad encode), Auto-Dial List (32 numbers 16-Digits each) & Stun.

³ Special Alert Tone Patterns operate for 2-Tone, DTMF, FleetSync® selective call decode.

⁴ Call Key: 6 keys max.; operates for 2-Tone, DTMF and FleetSync® status encode.

⁵ KPG-89D required: Windows®98/NT/2000/Me/XP compatible; English/Spanish screen languages.

⁶ Conventional Zones: 512 Channels/128 Zones max. per radio; 250 CH max. per Zone.

Trunked Zones: 512 GID/128 Zones max. per radio; 250 GID max. per Zone.

⁷ Two-Tone Decode (4 sets x 4 pairs each); Single / Two-Tone Encode (32 tones); Operator Selectable Tone (40 QT.DQT code pairs).

⁸ Kenwood LTR Features include: GID Delete/Add, LTR Talk Around /Scan Revert Group Display, System Scan, Group Scan, Auto Search.

⁹ FleetSync® & FleetSync® II are not compatible.

¹⁰ Short Text Messages are radio stored & LCD displayed.

KENWOOD



ADS#43407 Printed in USA